

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) Apparatus for use in a first device to receive digital data non-wirelessly from a second device and to transmit digital data non-wirelessly to the second device, the apparatus comprising:

a single jack configured to receive analog signals encoded with the digital data from the second device and to transmit analog signals encoded with digital data to the second device;

a first conversion unit coupled to the single jack and configured to encode digital data into analog signals for transmission to the second device; and

a second conversion unit coupled to the single jack and configured to recover the digital data from the analog signals received from the second device;

wherein the first device is one of a mobile phone, a personal digital assistant or a smart phone and wherein the second device is one of a mobile phone, a personal digital assistant or a smart phone.

2. (Original) The apparatus of claim 1, further comprising:

a non-wireless communication device configured to couple with the jack, the non-wireless communication device configured to carry the analog signals encoded with digital data to the first device using the jack.

3. (Original) The apparatus of claim 2, wherein the non-wireless communication device comprises:

a non-wireless medium having a first end and a second end;

a first plug coupled to said first end and configured to couple to the jack; and

a second plug coupled to said second end and configured to couple to a jack of the second device.

4. (Original) The apparatus of claim 1, wherein the jack is configured to couple to either one of a headphone or a headset.

5. (Original) The apparatus of claim 4, wherein the jack is configured to receive perceptible sound.

6. (Currently Amended) A method for use in a first device to receive digital data non-wirelessly from a second device and to transmit digital data non-wirelessly to the second device, the method comprising:

receiving analog signals encoded with the digital data from the second device using a single jack; and

recovering the digital data from the analog signals received from the second device;

encoding digital data into analog signals; and

transmitting the analog signals encoded with digital data to the second device using the single jack;

wherein the first device is one of a mobile phone, a personal digital assistant or a smart phone and wherein the second device is one of a mobile phone, a personal digital assistant or a smart phone.

7. (Original) The method of claim 6, further comprising:

coupling a non-wireless communication device to the jack; and

receiving the analog signals through the non-wireless communication device.

8. (Original) The method of claim 7, wherein receiving the analog signals comprises:

receiving the analog signals as audible analog signals.

9. (Original) The method of claim 7, wherein receiving the analog signals comprises:

receiving the analog signals electronically.

10. (Original) The method of claim 6, further comprising:

receiving perceptible sound using the jack.

11 - 20. (Canceled)

21. (Currently Amended) Apparatus for use in a first device to receive digital data non-wirelessly from a second device and to transmit digital data non-wirelessly to the second device, the apparatus comprising:

means for receiving through a single jack analog signals encoded with the digital data from the second device; and

means for recovering the digital data from the analog signals received from the second device;

means for encoding digital data into analog signals for transmission to the second device;
and

means for transmitting through the single jack analog signals encoded with digital data to the second device;

wherein the first device is one of a mobile phone, a personal digital assistant or a smart phone and wherein the second device is one of a mobile phone, a personal digital assistant or a smart phone.

22. (Original) The apparatus of claim 21, further comprising:

a non-wireless means for carrying the analog signals encoded with digital data to the first device using the jack.

23 - 33. (Cancelled)

34. (New) The apparatus of claim 1, wherein the first conversion unit is further configured to encode digital data based on multi-carrier modulation and the second conversion unit is further configured to recover digital data based on multi-carrier demodulation.

35. (New) The apparatus of claim 34, further comprising:

a sensor configured to detect whether a plug has been coupled to the single jack.

36. (New) The method of claim 6, further comprising:
recovering the digital data from the analog signals received from the second device based on multi-carrier demodulation; and
encoding digital data into analog signals for transmission to the second device based on multi-carrier modulation.
37. (New) The method of claim 36, further comprising:
detecting, via a sensor, whether a plug has been coupled to the single jack.
38. (New) The apparatus of claim 21, wherein
means for recovering the digital data from the analog signals received from the second device is based on multi-carrier demodulation; and
means for encoding digital data into analog signals for transmission to the second device is based on multi-carrier modulation.
39. (New) The apparatus of claim 38, further comprising:
means for detecting, via a sensor, whether a plug has been coupled to the single jack.